

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
24 June 2004 (24.06.2004)

PCT

(10) International Publication Number  
**WO 2004/053421 A1**

(51) International Patent Classification<sup>7</sup>: **F41H 7/04, 5/013**

Francois [ZA/AU]; PO Box 751, Strathfieldsaye, Victoria 3551 (AU).

(21) International Application Number:  
PCT/AU2003/001658

(74) Agent: **DI GIANTOMASSO, Donato, Franco**; Minter Ellison Patent Attorneys, Level 16, Rialto Towers, 525 Collins Street, Melbourne, Victoria 3000 (AU).

(22) International Filing Date:  
12 December 2003 (12.12.2003)

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
2002953287 12 December 2002 (12.12.2002) AU

(71) Applicant (*for all designated States except US*): **VALIR PTY LTD** [AU/AU]; PO Box 751, Strathfieldsaye, Victoria 3551 (AU).


(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): **DE WET, Jacobus,**

[Continued on next page]

(54) Title: PROTECTIVE APPARATUS FOR VEHICLES



(57) Abstract: The invention provides a protective apparatus for a vehicle, the apparatus comprising a structure of generally convex shape adapted to be fitted to or to form part of a vehicle, wherein: (a) the protective apparatus is capable of resisting a force applied to the structure; and (b) the apex of the apparatus is disposed generally in a direction that is opposed to the direction of travel or movement of the force applied to the apparatus.



**Declaration under Rule 4.17:**

- as to the identity of the inventor (Rule 4.17(i)) for all designations

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

- with international search report